
JM

Thermocouple wire and assemblies



Thermocouple wire and assemblies

Our customers trust us to provide them with accurate and reliable thermocouple products. We have earned that trust by consistently supplying high quality thermocouple wire and by providing greater value through investment in research and development.

We offer type R, type S and type B thermocouple wire, as well as other more specialised combinations. Thermocouples are calibrated in our UKAS accredited laboratory, in line with international standards. Our customers expect the best, so we ensure that we are providing products of the highest quality with a security of supply that can be depended upon.

Our research and development is always focussed on technologies that provide greater value for our customers, whether it is improving product lifetime, enhancing performance or reducing costs. This has most recently been demonstrated by our high strength HTXTM platinum thermocouple wire and long length mineral insulated thermocouples, available up to 18m.

Туре	Combination		Working temperature range (°C)			Tolerance
	-ve	+ve	Bare wire only Continuous use	Bare wire only Intermittent use	Mineral insulated form	
5	Pt	10% RhPt	200-1500	200-1650	200-1300	IEC 584-2 Class 1
3	Pt	13% RhPt	200-1500	200-1650	200-1300	IEC 584-2 Class 1
В	6% RhPt	30% RhPt	200-1600	200-1750	200-1450	IEC 584-2 Class 2
	20% RhPt	40% RhPt	200-1700	200-1850	200-1450	8.0°C
	Iridium	40% IrRh	1000-2100		N/A	10.0°C
	0.03% FeAu	Chromel	1-300 K		N/A	

For more information about our HTX™ platinum thermocouple please visit our website.

Europe

Tel: +44 1763 253000 Fax: +44 1763 253313 Email: nobleuk@matthey.com USA

Tel: +1 610 648 8000 Fax: +1 610 648 8105 Email: nobleww@jmusa.com Asia

Tel: +852 2738 0380 Fax: +852 2736 2222

Email: jmhk@mattheyasia.com

